

AGRIMAX RT-955 (Row Crop 95 Series) - Tractor Radial Tyres

SIZE	RIM		Section Width	Overall Diameter	Static Loaded Radius	Rolling Circumference	SRI	bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
	REC.	ALT.						km/h	Load capacity (kg / tyre)												
	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)															
230/95 R 32 128A8 / B (Replaces 9.5 R 32)	W8	W7	238	1251	585	3792	600	50	-	705	-	920	-	1120	1225	1300	1425	1550	1675	1800	-
								40	-	705	-	920	-	1120	1225	1300	1425	1550	1675	1800	-
								30	-	755	-	985	-	1200	1315	1390	1525	1660	1795	1930	-
								10	-	840	-	1055	-	1300	1540	1785	1840	2055	2270	2485	2700
270/95 R 32 136A8 / B (Replaces 11.2 R 32)	W9	W8 W10	275	1327	614	4044	625	50	-	875	-	1145	-	1390	1525	1615	1770	1930	2085	2240	-
								40	-	875	-	1145	-	1390	1525	1615	1770	1930	2085	2240	-
								30	-	940	-	1225	-	1490	1635	1730	1900	2065	2235	2400	-
								10	-	1045	-	1315	-	1615	1920	2220	2285	2555	2825	3095	3360
230/95 R 36 130A8 / B (Replaces 9.5 R 36)	W8	W7	238	1352	639	4112	650	50	-	745	-	970	-	1180	1295	1370	1505	1635	1770	1900	-
								40	-	745	-	970	-	1180	1295	1370	1505	1635	1770	1900	-
								30	-	795	-	1040	-	1265	1385	1470	1610	1755	1895	2035	-
								10	-	885	-	1115	-	1370	1625	1885	1940	2170	2395	2625	2850
270/95 R 36 139A8 / B (Replaces 11.2 R 36)	W9	W8 W10	275	1428	665	4368	675	50	-	950	-	1240	-	1510	1655	1750	1920	2090	2260	2430	-
								40	-	950	-	1240	-	1510	1655	1750	1920	2090	2260	2430	-
								30	-	1020	-	1330	-	1620	1775	1880	2060	2245	2425	2605	-
								10	-	1130	-	1425	-	1750	2080	2410	2480	2775	3065	3355	3645
270/95 R 38 140A8 / B (Replaces 11.2 R 38)	W9	W8 W10	275	1479	697	4510	700	50	-	975	-	1275	-	1550	1700	1800	1975	2150	2325	2500	-
								40	-	975	-	1275	-	1550	1700	1800	1975	2150	2325	2500	-
								30	-	1045	-	1365	-	1660	1820	1930	2115	2305	2490	2675	-
								10	-	1165	-	1465	-	1800	2140	2475	2550	2850	3150	3450	3750
230/95 R 42 133A8 / B (Replaces 9.5 R 42)	W8	W7	238	1506	706	4518	725	50	-	805	-	1055	-	1280	1405	1485	1630	1775	1920	2060	-
								40	-	805	-	1055	-	1280	1405	1485	1630	1775	1920	2060	-
								30	-	860	-	1125	-	1370	1500	1590	1745	1900	2055	2205	-
								10	-	960	-	1210	-	1485	1765	2040	2105	2350	2600	2845	3090
300/85 R 42 144A8 / B (Replaces 11.2 R 42)	W 9	W10 W11	295	1577	745	4850	750	50	-	1150	-	1485	-	1795	1960	2100	2300	2495	2660	2800	-
								40	-	1150	-	1485	-	1795	1960	2100	2300	2495	2660	2800	-
								30	-	1230	-	1590	-	1920	2100	2250	2460	2670	2850	3000	-
								10	-	1305	-	1640	-	2020	2395	2775	2860	3195	3530	3865	4200
230/95 R 44 134A8 / B (Replaces 9.5 R 44)	W8	W7	238	1556	739	4788	750	50	-	830	-	1085	-	1315	1445	1530	1675	1825	1975	2120	-
								40	-	830	-	1085	-	1315	1445	1530	1675	1825	1975	2120	-
								30	-	890	-	1160	-	1410	1545	1635	1795	1955	2115	2270	-
								10	-	990	-	1245	-	1530	1815	2100	2165	2420	2675	2930	3180

AGRIMAX RT-955 (Row Crop 95 Series) - Tractor Radial Tyres

SIZE	RIM		Section Width	Overall Diameter	Static Loaded Radius	Rolling Circumference	SRI	bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
	REC.	ALT.						km/h	Load capacity (kg / tyre)												
	(mm)	(mm)	(mm)	(mm)	(mm)																
270/95 R 44 142A8 / B (Replaces 11.2 R 44)	W9	W8 W10	275	1632	764	4983	775	50	-	1035	-	1355	-	1645	1805	1910	2095	2280	2465	2650	-
								40	-	1035	-	1355	-	1645	1805	1910	2095	2280	2465	2650	-
								30	-	1110	-	1450	-	1765	1935	2045	2245	2445	2645	2840	-
								10	-	1235	-	1555	-	1910	2270	2625	2705	3025	3340	3660	3975
300/95 R 46 148A8 / B (Replaces 12.4 R 46)	W9	W10 W11 DW10 DW11	295	1738	812	5318	825	50	1105	1295	1485	1670	1860	2020	2205	2365	2585	2805	2995	3150	-
								40	1105	1295	1485	1670	1860	2020	2205	2365	2585	2805	2995	3150	-
								30	1185	1385	1590	1790	1995	2160	2365	2535	2770	3005	3210	3375	-
								20	1360	1590	1825	2055	2290	2480	2715	2910	3180	3450	3685	3875	-
10	1525	1785	2045	2310	2570	2785	3045	3265	3570	3875	4135	4350	4725								
230/95 R 48 136A8 / B (Replaces 9.5 R 48)	W8	W7	238	1656	792	5085	800	50	-	875	-	1145	-	1390	1525	1615	1770	1930	2085	2240	-
								40	-	875	-	1145	-	1390	1525	1615	1770	1930	2085	2240	-
								30	-	940	-	1225	-	1490	1635	1730	1900	2065	2235	2400	-
								10	-	1045	-	1315	-	1615	1920	2220	2285	2555	2825	3095	3360
270/95 R 48 144A8 / B (Replaces 11.2 R 48)	W9	W8 W10	275	1733	820	5351	825	50	-	1095	-	1430	-	1740	1905	2020	2215	2410	2605	2800	-
								40	-	1095	-	1430	-	1740	1905	2020	2215	2410	2605	2800	-
								30	-	1170	-	1530	-	1860	2040	2160	2370	2580	2790	3000	-
								10	-	1305	-	1640	-	2020	2395	2775	2860	3195	3530	3865	4200
340/85 R 48 152A8 / B (Replaces 13.6 R 48)	W12	W11	353	1797	855	5572	875	50	-	1385	-	1815	-	2205	2415	2560	2805	3055	3305	3550	-
								40	-	1385	-	1815	-	2205	2415	2560	2805	3055	3305	3550	-
								30	-	1485	-	1940	-	2360	2585	2740	3005	3270	3535	3800	-
								10	-	1655	-	2080	-	2560	3040	3515	3625	4050	4475	4900	5325
300/95 R 52 151A8 / B (Replaces 12.4 R 52)	W9	DW10 W10 W11 DW11	295	1891	889	5822	925	50	-	1350	-	1760	-	2140	2350	2485	2730	2970	3210	3450	-
								40	-	1350	-	1760	-	2140	2350	2485	2730	2970	3210	3450	-
								30	-	1445	-	1885	-	2295	2515	2665	2920	3180	3440	3695	-
								10	-	1605	-	2020	-	2485	2950	3420	3520	3935	4350	4765	5175
270/95 R 54 146A8 / B (Replaces 11.2 R 54)	W8	W9 W10	265	1885	887	5655	925	50	-	1170	-	1530	-	1860	2040	2160	2370	2580	2790	3000	-
								40	-	1170	-	1530	-	1860	2040	2160	2370	2580	2790	3000	-
								30	-	1255	-	1640	-	1995	2185	2315	2540	2765	2990	3210	-
								10	-	1395	-	1755	-	2160	2565	2970	3060	3420	3780	4140	4500

Tolerances: Overall Diameter +/-2% | Section Width +/-2% | Rolling Circumference +/-2.5%