

## Lawn & Garden Tyres

Tyre size	Pattern	Rim		Unloaded inflated Dimensions		Static Loaded Radius (mm)	Rolling circumference (± 2.5 %) (mm)	Ply Rating	Type	Load Capacity		Inflation Pressure (bar)
				± 2 %						15 km/h Max. Load (kgs)		
		Rec.	Alt.	Section Width (mm)	Overall Diameter (mm)							
11 X 4.00 - 5	LG-306	3.00 A	---	104	272	120	789	4	TL	150	3.2	
13 X 5.00 - 6	LG-306	3.50 A	---	127	325	144	943	4	TL	200	2.8	
								6*	TL	255	4.2	
15 X 6.00 - 6	LG-306	4.50 A	---	152	365	159	1059	4	TL	257	2.1	
								6*	TL	335	3.2	
16 X 6.50 - 8	LG-306	5.375 I-55; I-70; I-90	----	170	408	182	1183	4	TL	280	1.9	
								6*	TL	355	2.9	
18 X 8.50 - 8	LG-306	7.00 I-55; I-70; I-90	----	215	450	198	1305	4	TL	375	1.5	
								6*	TL	475	2.3	
18 X 9.50 - 8	LG-306	7.00 I-55; I-70; I-90	----	230	470	206	1363	4	TL	470	1.7	
								6*	TL	605	2.5	
20 X 10.00 - 8	LG-306	8.00 I-55	7.00 I-55 I-70, I-90	254	508	221	1473	4	TL	540	1.5	
								6*	TL	670	2.2	
18 X 8.50 - 10	LG-306	7.00 I-55; I-70; I-90	----	210	460	209	1340	4	TL	361	1.5	
20 X 8.00 - 10	LG-306	6.00 I-55; I-70; I-90	6JA	205	500	223	1450	4	TL	410	1.7	
								6	TL	510	2.5	
20 X 10.00 - 10	LG-306	8.00 I-55	7.00 I-55	250	508	226	1473	4	TL	530	1.5	
								6*	TL	660	2.2	
23 X 8.50 - 12	LG-306	7.00 I-55; I-70; I-90	7JA	210	575	258	1668	4	TL	510	1.5	
								6*	TL	655	2.3	
								8	TL	765	3.0	
								12	TL	960	4.5	

## Lawn & Garden Tyres

Tyre size	Pattern	Rim		Unloaded inflated Dimensions		Static Loaded Radius (mm)	Rolling circumference (± 2.5 %) (mm)	Ply Rating	Type	Load Capacity		Inflation Pressure (bar)
				± 2 %						15 km/h Max. Load (kgs)		
		Rec.	Alt.	Section Width (mm)	Overall Diameter (mm)							
23 X 10.50 - 12	LG-306	8.5 I-55	7.00 I-55 I-70, I-90	260	585	262	1697	4	TL	610	1.4	
								6*	TL	800	2.2	
								8	TL	955	3.0	
								12	TL	1215	4.5	
24 X 12.00 - 12	LG-306	9.5 AT	9.0 AT; 8.5 AT; 8.0 AT	298	610	276	1774	4	TL	775	1.4	
26 X 12.00 - 12	LG-306	10.50 I-55; I-70; I-90	10 1/2 JA; 8 1/2 JA	310	640	283	1856	4	TL	800	1.4	
								6*	TL	1060	2.2	
								8	TL	1265	3.0	
								12	TL	1600	4.5	
24 X 8.50 - 14	LG-306	7.00 JA	---	210	610	280	1769	4	TL	550	1.6	
25 X 8.50 - 14	LG-306	7.00 I-55; I-70; I-90	----	220	638	333	1914	6	TL	750	2.2	
27 X 8.50 - 15	LG-306	7.00 JA	---	216	680	308	1970	4 #	TL	560	2.1	
27 X 10.5 - 15	LG-306	8.00 LB	---	272	705	318	2042	4 #	TL	600	2.1	
31/15.5 - 15	LG-306	13.00 LB	---	391	792	350	2313	4	TL	775	1.4	
13.6 - 16	LG-306	W12	W11	388	975	414	2847	4	TL	950	1.0	
33 X 15.50 - 16.5	LG-306	12.00	---	396	840	374	2453	10	TL	1630	2.1	
38 X 14 - 20	LG-306	W 11	W 11 H	375	980	435	2894	4 #	TL	1050	1.7	
44 X 18 - 20	LG-306	W 14L	W 14 LH	475	1180	543	3496	4 #	TL	1500	1.4	

All tyres conform to ETRTO or STRO standards

\* Also available in Aramid Belted Construction

# These loads are for 50 Km/h