

AT 111 HD - Technical Specifications



Description

AT 111 HD is suitable for all-terrain sport racing with

ATVs. The increased tread depth and the thick sidewall

provide extra grip and braking control in addition to

extraordinary traction and high-speed control in power slides. AT 111 HD ensures an extended tire life-cycle.

UM International Standard

Construction BIAS

Machinery Agriculture: ATV

Version STANDARD

Type TL

Tyre Size AT 20 X 11 - 10

Dimensions International Standard

Ply Rating	6
Section Width (mm)	279
Overall Diameter (mm)	505
Rim Rec	9.0 AT
Rim Alt	8.5 AT
ECE	E4-75R-0006327

Load capacity (Kg)

km/h / bar	0.45
100	150

Printed on 05/04/2022 17:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..