DATA SHEET

Latest update
4-08-2026



ROCK GRIP IND4 (ECH)

TYRE SIZE	**14.00 - 24**
UM	IS STANDARD
MACHINERY	EMPTY CONTAINER HANDLER
VERSION	PORT INDUSTRIAL
TL/TT	TL

DIMENSIONS IS STANDARD

OW (MM)	375	**RIM ALT**	10.00 VA
OD (MM)	1410	**PR**	32
SLR (MM)	647	**TRA CODE**	IND4
RC (MM)	4173	**TREAD DEPTH (MM)**	50,5
RIM REC	10.00 WA		

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	10.00
10	14175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.