

EARTHMAX SR 51 - Technical Specifications

LI/SS

Description EARTHMAX SR 51 (L-5) is an *All Steel* radial tire specially

designed for loaders or dozers. EARTHMAX SR 51 is ideal for severe operations requiring added cut resistance,

sidewall protection and exceptional traction.

UM International Standard

Construction RADIAL

Machinery OTR: Dozer, Loader

186 A2

Version CUT RESISTANT COMPOUND

Type TL

Tyre Size 20.5 R 25



Dimensions International Standard

Overall Width (mm)	539
Overall Diameter (mm)	1545
Static Loaded Radius (mm)	703
Rolling Circumference (mm)	4650
Rim Rec	17.00/2.0
Rim Alt	17.00AL/1.7
Star Rating	*
TRA Code	L5

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00
10	8000	8250	8750	9000	9500

Printed on 05/04/2022 18:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..

	-			