

## LG 307 - Technical Specifications



**Description** LG 307 is a lawn and garden tire suitable for mowers.

The specific tread pattern makes the tire gentle on the ground to prevent turf damages, easing handling at the

same time.

UM International Standard

Construction BIAS

Machinery Agriculture: Mower

Version STANDARD

Type TL

Tyre Size 20 X 10.00 - 8

## **Dimensions International Standard**

Ply Rating	6
Section Width (mm)	255
Overall Diameter (mm)	495
Static Loaded Radius (mm)	215
Rolling Circumference (mm)	1435
Rim Rec	8.00   - 55 ;   - 70 ;   - 90
Rim Alt	7.00   - 55 ;   - 70 ;   - 90
ECE	E11-106R-003462

## Load capacity (Kg)

km/h / bar	2.20
15	670

Printed on 25/09/2020 15:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..