

## LG 306 - Technical Specifications



**Description** LG 306 is a lawn and garden tire suitable for mowers. In

some sizes, LG 306 is also fit for small tractors. The specific tread pattern makes the tire gentle on the ground, easing handling at the same time. LG 306 is available in an "aramid-belted" version for users who

need strengthened puncture resistance.

UM International Standard

Construction BIAS

Machinery Agriculture: Mower, Small Tractor

Version STANDARD

Type TL

Tyre Size 20 x 8.00 - 10

## **Dimensions International Standard**

| Ply Rating                 | 6                             |
|----------------------------|-------------------------------|
| Section Width (mm)         | 205                           |
| Overall Diameter (mm)      | 500                           |
| Static Loaded Radius (mm)  | 223                           |
| Rolling Circumference (mm) | 1450                          |
| Rim Rec                    | 6.00   - 55 ;   - 70 ;   - 90 |
| Rim Alt                    | 6 JA                          |
| ECE                        | E11-106R-003456               |

## Load capacity (Kg)

| km/h / bar | 2.50 |
|------------|------|
| 15         | 510  |

Printed on 25/09/2020 15:24

| permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd |
|--|
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |