

GF 305 FARM TRAILER - Technical Specifications



Description GF 305 FARM TRAILER has been designed for

implements in transport operations. This tire is naturally

gentle on the ground and protects the field against

damage.

UM International Standard

Construction BIAS

Machinery Agriculture: Implement Machinery

 Version
 STANDARD

 Type
 TL

 Tyre Size
 205/65 - 10 (20.5 x 8.00 - 10)

Dimensions International Standard

Ply Rating	10
Section Width (mm)	212
Overall Diameter (mm)	520
Static Loaded Radius (mm)	223
Rolling Circumference (mm)	1508
Rim Rec	6.00
ECE	E11-106R-003578

Load capacity (Kg)

km/h / bar	6.20
40	695

Printed on 25/09/2020 13:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..