

MAGLIFT - Technical Specifications



Description

MAGLIFT has been particularly designed for forklift in industrial and logistic operations. This solid tire features high load capacity and outstanding comfort. MAGLIFT shows excellent cut and chip resistance resulting in a long tire life. Its reinforced structure eliminates slippage risks whilst the special bead shape simplifies mounting operations on the rim.

UM

International Standard

Construction

SOLID

Machinery

Industrial: Forklift

| | |
|---------|----------|
| Version | STANDARD |
|---------|----------|

| | |
|------|--|
| Type | |
|------|--|

| | |
|-----------|----------------------------|
| Tyre Size | 18 X 7 - 8 (180/70 - 8) |
|-----------|----------------------------|

Dimensions International Standard

| | |
|------|---|
| TKPH | 1 |
|------|---|

| | |
|--------------------|-----|
| Section Width (mm) | 153 |
|--------------------|-----|

| | |
|-----------------------|-----|
| Overall Diameter (mm) | 457 |
|-----------------------|-----|

| | |
|---------|------------|
| Rim Rec | 4.33 R - 8 |
|---------|------------|

Load capacity (Kg)

| | km/h / bar | |
|----------------|------------|------|
| 25 LOAD WHEEL | | 2145 |
| 25 STEER WHEEL | | 1650 |