

## FL 252 - Technical Specifications



### Description

FL 252 is a tire suitable for hay harvesting applications with rotor rakes/tedders as well as for logistic operations using forklifts. This tire provides excellent durability while the specific tread pattern ensures maximum stability during lifting operations.

### UM

International Standard

### Construction

BIAS

### Machinery

Agriculture: Rotor Rake / Tedder  
Industrial: Forklift

Version	STANDARD
Type	TT
Tyre Size	6.50 - 10

### Dimensions International Standard

Ply Rating	10
Section Width (mm)	185
Overall Diameter (mm)	605
Rim Rec	5.00 F
Rim Alt	5.50 F

### Load capacity (Kg)

km/h / bar	
25 LOAD WHEEL	1950
25 STEER WHEEL	1500
10 OTHER VEHICLES	1950
25 OTHER VEHICLES	1500
STATIC SIDE LOADER	2265

Printed on 06/04/2022 10:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..

