

## SKID POWER HD - Technical Specifications



### Description

SKID POWER HD has been designed for skid steers in construction applications. The tire features an extra deep tread and sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER HD is the ideal tire for loose surfaces and heavy-duty service.

### UM

International Standard

### Construction

BIAS

### Machinery

Industrial: Skid Steer

Version	STANDARD
Type	TL
Tyre Size	23 X 8.50 - 12

### Dimensions International Standard

Ply Rating	6
Section Width (mm)	215
Overall Diameter (mm)	585
Static Loaded Radius (mm)	267
Rolling Circumference (mm)	1795
Rim Rec	7.00 I - 55
Rim Alt	7.00 I - 70 ; 7 JA

### Load capacity (Kg)

km/h / bar	
	3.40
10	820
15	650
25	600

*its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*