

## SKID POWER (CHEVRON) - Technical Specifications



**Description** SKID POWER (CHEVRON) has been specially designed

for skid steers in construction applications. It features excellent traction as well as enhanced self-cleaning properties. SKID POWER (CHEVRON) is particularly suitable for loose surfaces and shows high cut and chip

resistance.

UM International Standard

Construction BIAS

Machinery Industrial: Skid Steer

Version STANDARD

Type TL

Tyre Size 7.00 - 15

## **Dimensions International Standard**

| Ply Rating                 | 6      |
|----------------------------|--------|
| Section Width (mm)         | 203    |
| Overall Diameter (mm)      | 762    |
| Static Loaded Radius (mm)  | 347    |
| Rolling Circumference (mm) | 2295   |
| Rim Rec                    | 5.50 F |
| Rim Alt                    | 6 LB   |

## Load capacity (Kg)

| km/h / bar | 4.10 |
|------------|------|
| 10         | 1440 |
| 15         | 1140 |

Printed on 24/09/2020 12:25

| permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd |
|--|
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |
|  |