

MAGLIFT - Technical Specifications



Description

MAGLIFT has been particularly designed for forklift in industrial and logistic operations. This solid tire features high load capacity and outstanding comfort. MAGLIFT shows excellent cut and chip resistance resulting in a long tire life. Its reinforced structure eliminates slippage risks whilst the special bead shape simplifies mounting operations on the rim.

UM

International Standard

Construction

SOLID

Machinery

Industrial: Forklift

| | |
|-----------|-----------------|
| Version | LIP NON MARKING |
| Type | |
| Tyre Size | 8.25 - 15 |

Dimensions International Standard

| | |
|-----------------------|----------|
| Section Width (mm) | 207 |
| Overall Diameter (mm) | 818 |
| Rim Rec | 6.5 - 15 |

Load capacity (Kg)

| | km/h / bar | |
|----------------|------------|------|
| 25 LOAD WHEEL | | 4750 |
| 25 STEER WHEEL | | 3650 |

Printed on 23/09/2020 18:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..