

SKID POWER HD - Technical Specifications

Description



	construction applications. The tire features an extra deep tread and sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER HD is the ideal tire for loose surfaces and heavy-duty service.
UM	International Standard
Construction	BIAS
Machinery	Industrial: Skid Steer
Version	STANDARD
Туре	TL
Tyre Size	27 X 8.50 - 15

SKID POWER HD has been designed for skid steers in

Dimensions International Standard

Ply Rating	8
Section Width (mm)	218
Overall Diameter (mm)	676
Static Loaded Radius (mm)	313
Rolling Circumference (mm)	1995
Rim Rec	7 <i>J</i> A

Load capacity (Kg)

km/h / bar	4.20
10	1310
15	1035
25	955

Printed on 24/09/2020 12:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without

prior written consent by Balkrishna Industries Ltd..