

SKID POWER HD - Technical Specifications



Description SKID POWER HD has been designed for skid steers in

construction applications. The tire features an extra deep tread and sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER HD is the ideal tire for loose surfaces and heavy-duty

service.

UM International Standard

Construction BIAS

Machinery Industrial: Skid Steer

Version	STANDARD
Туре	TL
Tyre Size	27 X 10.5 - 15

Dimensions International Standard

Ply Rating	8
Section Width (mm)	256
Overall Diameter (mm)	684
Static Loaded Radius (mm)	316
Rolling Circumference (mm)	2020
Rim Rec	8 LB

Load capacity (Kg)

km/h / bar	4.20
10	1405
15	1110
25	1025

Printed on 24/09/2020 12:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without

