

SURE TRAX HD - Technical Specifications



Description	SURE TRAX HD is a block pattern tire for skid steers in construction applications. It shows excellent cut and chip resistance as well as top rim protection. SURE TRAX HD is ideal for paved surfaces and heavy-duty service.
UM	International Standard
Construction	BIAS
Machinery	Industrial: Skid Steer
Version	STANDARD
Туре	TL
Tyre Size	10 - 16.5

Dimensions International Standard

Ply Rating	10
Section Width (mm)	268
Overall Diameter (mm)	785
Static Loaded Radius (mm)	359
Rolling Circumference (mm)	2316
Rim Rec	8.25
ECE	

Load capacity (Kg)

km/h / bar	5.20
10	2135
15	1685
25	1560

Printed on 24/09/2020 12:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without

prior written consent by Balkrishna Industries Ltd..