

SKID POWER HD - Technical Specifications



Description	SKID POWER HD has been designed for skid steers in construction applications. The tire features an extra deep tread and sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER HD is the ideal tire for loose surfaces and heavy-duty service.	
UM	International Standard	
Construction	BIAS	
Machinery	Industrial: Skid Steer	
Version	STANDARD	
Туре	TL	
Tyre Size	15 - 19.5	

Dimensions International Standard

Ply Rating	14
Section Width (mm)	400
Overall Diameter (mm)	1035
Static Loaded Radius (mm)	468
Rolling Circumference (mm)	3053
Rim Rec	11.75
Rim Alt	12.25

Load capacity (Kg)

km/h / bar	4.85
10	4565
15	3605
25	3330

Printed on 24/09/2020 12:42

its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd.