

AGRIMAX RT 955 - Technical Specifications



Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Sprayer, Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	230/95 R 32 (9.5 R 32)
LI/SS	128 A8/B

Dimensions International Standard

Section Width (mm)	238
Overall Diameter (mm)	1251
Static Loaded Radius (mm)	585
Rolling Circumference (mm)	3792
Rim Rec	W 8
Rim Alt	W 7
ECE	E4-106R-000764
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	705	920	1120	1225	1300	1425	1550	1675	1800	-
40	705	920	1120	1225	1300	1425	1550	1675	1800	-
30	755	985	1200	1315	1390	1525	1660	1795	1930	-
10	840	1055	1300	1540	1785	1840	2055	2270	2485	2700

Printed on 22/09/2020 13:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..