



## ***AGRIMAX FORTIS - Technical Specifications***



### ***Description***

AGRIMAX FORTIS is your reliable partner for all preparation, soil tillage and haulage operations. Designed to equip the latest, most modern and most powerful tractors, AGRIMAX FORTIS allows you to carry very high loads reaching up to 65 km/h (40 MPH). It ensures outstanding traction along with top handling and best comfort for a perfect driving experience. The tire has been designed with a reinforced nylon casing for enhanced productivity in the fields preserving the soil thanks to reduced compaction.

### ***UM***

International Standard

### ***Construction***

RADIAL

### ***Machinery***

Agriculture: High-Power Tractor, Sprayer, Tractor

<i>Version</i>	STANDARD
<i>Type</i>	TL
<i>Tyre Size</i>	600/70 R 34
<i>LI/SS</i>	160 D/163 A8

### ***Dimensions International Standard***

<i>Section Width (mm)</i>	591
<i>Overall Diameter (mm)</i>	1704
<i>Static Loaded Radius (mm)</i>	761
<i>Rolling Circumference (mm)</i>	5109
<i>Rim Rec</i>	DW 18 L
<i>Rim Alt</i>	DW 20 B ; W 18 L
<i>ECE</i>	E4-106R-001401
<i>TRA Code</i>	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2160	2520	2835	3150	3465	3735	4140	4500
50	2270	2650	2980	3310	3640	3925	4350	4725
40	2340	2730	3075	3415	3755	4050	4485	4875
30	2485	2900	3265	3625	3985	4300	4765	5175
10 LT	2895	3380	3800	4225	4645	5005	5550	6030
10 HT	2485	2900	3265	3625	3985	4300	4765	5175

Printed on 21/09/2020 18:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..