

# RIDEMAX IT 697 (M+S)

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TYRE SIZE    | 600/65 R 38 IND                                                                          |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRACTOR                                                                                  |
| VERSION      | STANDARD                                                                                 |
| TYRE TYPE    | TL                                                                                       |
| LI/SS        | 166 D ; 170 A8                                                                           |



## DIMENSIONS IS STANDARD

|          |      |         |                 |
|----------|------|---------|-----------------|
| SW (MM)  | 590  | RIM REC | DW 18 L         |
| OD (MM)  | 1745 | RIM ALT | DW 20 B         |
| SLR (MM) | 795  | ECE     | E11-106R-005855 |
| RC (MM)  | 5315 | SRI     | 825             |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  |
|------------|------|------|------|------|------|------|
| 65         | 2490 | 3075 | 3605 | 4185 | 4715 | 5300 |
| 50         | 2690 | 3320 | 3895 | 4525 | 5095 | 5725 |
| 40         | 2820 | 3480 | 4080 | 4740 | 5340 | 6000 |
| 30         | 2990 | 3690 | 4325 | 5025 | 5660 | 6360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.