


# AGRIMAX V-FLECTO



<b>TYRE SIZE</b>	<b>VF 650/75 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	175 D

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	675	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	1941	<b>RIM ALT</b>	DW 21 B
<b>SLR (MM)</b>	833	<b>ECE</b>	E11-106R-0010663
<b>RC (MM)</b>	5796	<b>SRI</b>	925

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	3450	4015	4580	5145	5710	6275
<b>FROM 65 TO 40</b>	3795	4415	5035	5655	6275	6900
30	3865	4500	5135	5765	6400	7035
20	3945	4590	5235	5880	6525	7175
10	4170	4855	5540	6220	6905	7590
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	5310	6180	7050	7920	8790	9660
10HT	3865	4500	5135	5765	6400	7035

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.