

AGRIMAX V-FLECTO

TYRE SIZE	VF 480/80 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TYRE TYPE	TL



DIMENSIONS IS STANDARD

SW (MM)	479	RIM REC	DW 16 L
OD (MM)	1840	RIM ALT	DW 15 L
SLR (MM)	826	ECE	E11-106R-0010410
RC (MM)	5465	SRI	875

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2	2.4
70	2395	2755	3160	3570	3975	4385	4790	5095
FROM 65 TO 40	2635	3025	3475	3920	4370	4820	5265	5600
30	2685	3085	3545	4000	4455	4915	5370	5710
20	2740	3145	3610	4075	4540	5010	5475	5820
10	2900	3330	3820	4315	4805	5300	5795	6160
UPTO 10 CYC	3910	4495	5160	5825	6490	7155	7820	8315
10HT	2685	3085	3545	4000	4455	4915	5370	5710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.