

AGRIMAX TERIS - Technical Specifications



Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle – also in harsh conditions and if there are stubbles in the fields.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Cotton Picker, Harvester

Version	STANDARD
Type	TL
Tyre Size	520/85 R 42
LI/SS	168 D

Dimensions International Standard

Section Width (mm)	516
Overall Diameter (mm)	1951
Static Loaded Radius (mm)	890
Rolling Circumference (mm)	5851
Rim Rec	DW 16 L
Rim Alt	DD 18 L
ECE	E4-106R-001829

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.8
65	1850	2185	2520	2800	3140	3420	3980	4540	5100	5600	-
50	1945	2295	2650	2940	3295	3590	4175	4765	5355	5880	-
40	2025	2395	2765	3070	3440	3745	4360	4970	5585	6135	-
30	2130	2515	2900	3220	3610	3930	4575	5250	5865	6440	-
25	2195	2590	2990	3320	3720	4055	4715	5380	6045	6640	-
10	2775	3280	3780	4200	4705	5125	5965	6805	7645	8400	-
10 Cyclic	-	-	-	-	-	-	-	-	-	-	9520

Printed on 22/09/2020 15:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..