


# AGRIMAX SPARGO SB

<b>TYRE SIZE</b>	<b>VF 270/95 R 54</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STEEL BELTED
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	157 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	280	<b>RIM REC</b>	W9
<b>OD (MM)</b>	1900	<b>ECE</b>	E11-106R-0010833
<b>SLR (MM)</b>	895	<b>SRI</b>	900
<b>RC (MM)</b>	5843		

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1765	1995	2220	2405	2670	2820	3080	3345	3570	3755
FROM 65 TO 40	1940	2190	2435	2640	2930	3095	3385	3675	3920	4125
30	1980	2235	2485	2695	2990	3160	3455	3750	4000	4210
20	2020	2275	2535	2750	3050	3220	3520	3820	4080	4290
10	2135	2410	2680	2910	3225	3405	3725	4045	4315	4540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.