

## EARTHMAX SR 45 - Technical Specifications



<b>Description</b>	EARTHMAX SR 45 is an <i>All Steel</i> radial tire specially designed for rigid haul trucks. EARTHMAX SR 45 is the ideal tire for all operations requiring high traction.
<b>UM</b>	International Standard
<b>Construction</b>	RADIAL
<b>Machinery</b>	OTR: Rigid Dump Truck

<b>Version</b>	CUT RESISTANT COMPOUND
<b>Type</b>	TL
<b>Tyre Size</b>	18.00 R 33
<b>LI/SS</b>	191 B

### Dimensions International Standard

<b>TKPH</b>	185
<b>Overall Width (mm)</b>	505
<b>Overall Diameter (mm)</b>	1870
<b>Static Loaded Radius (mm)</b>	856
<b>Rolling Circumference (mm)</b>	5608
<b>Rim Rec</b>	13.00/2.5
<b>Rim Alt</b>	--
<b>Star Rating</b>	**
<b>TRA Code</b>	E4

### Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	8500	8750	9000	9250	9750	10000	10300	10600	10900

*permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*