

## LG 306 - Technical Specifications



**Description** LG 306 is a lawn and garden tire suitable for mowers. In

some sizes, LG 306 is also fit for small tractors. The specific tread pattern makes the tire gentle on the ground, easing handling at the same time. LG 306 is available in an "aramid-belted" version for users who

need strengthened puncture resistance.

UM International Standard

Construction BIAS

Machinery Agriculture: Mower, Small Tractor

Version STANDARD

Type TL

Tyre Size 18 X 9.50 - 8

## **Dimensions International Standard**

Ply Rating	6	
Section Width (mm)	230	
Overall Diameter (mm)	470	
Static Loaded Radius (mm)	206	
Rolling Circumference (mm)	1363	
Rim Rec	7.00   - 55 ;   - 70 ;   - 90	
ECE	E4-106R-002176	

## Load capacity (Kg)

km/h / bar	2.50
15	605

Printed on 25/09/2020 15:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..