

AW 708 - Technical Specifications



Description	AW 708 has been developed for soil tillage, transport and hay harvesting applications with implement machinery, trailers and balers. An HD version is available with a special cut-and-chip resistant compound.
UM	International Standard
Construction	BIAS
Machinery	Agriculture: Baler, Implement Machinery, Trailer Industrial: Trailer

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	19.0/45 - 17

Dimensions International Standard

Ply Rating	22
Section Width (mm)	491
Overall Diameter (mm)	866
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2536
Rim Rec	16.00
ECE	E11-106R-003636

Load capacity (Kg)

km/h / bar	
	3.90
10 FR	4970
25 FR	4225
30 FR	3975
40 FR	3550

its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..