

## AW 708 - Technical Specifications



<b>Description</b>	AW 708 has been developed for soil tillage, transport and hay harvesting applications with implement machinery, trailers and balers. An HD version is available with a special cut-and-chip resistant compound.
<b>UM</b>	International Standard
<b>Construction</b>	BIAS
<b>Machinery</b>	Agriculture: Baler, Implement Machinery, Trailer Industrial: Trailer

Version	STANDARD
Type	TL
Tyre Size	500/65 - 17

### Dimensions International Standard

Ply Rating	18
Section Width (mm)	520
Overall Diameter (mm)	1070
Static Loaded Radius (mm)	462
Rolling Circumference (mm)	3135
Rim Rec	16.0
ECE	E11-106R-004549

### Load capacity (Kg)

km/h / bar	
	3.50
10 FR	6300
25 FR	5355
30 FR	5040
40 FR	4500

*its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*