

RIB 774 (B) - Technical Specifications



Description

RIB 774 (B) is a low-section implement tire. It is ideal for modern farming and suitable for on- and off-the-road applications with implement machinery and trailers. It features great load capacity and a long tire life-cycle. An "HD" version is available for heavy-duty services.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Implement Machinery, Trailer
Industrial: Trailer

Version	STANDARD
Type	TL
Tyre Size	12.0 - 18 (340/70 - 18)

Dimensions International Standard

Ply Rating	16
Section Width (mm)	342
Overall Diameter (mm)	902
Static Loaded Radius (mm)	414
Rolling Circumference (mm)	2688
Rim Rec	11.0

Load capacity (Kg)

km/h / bar	
	5.20
10 FR	4690
25 FR	3985
30 FR	3750
40 FR	3350

its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..