

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Tractor, Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	420/65 R 28
LI/SS	135 D/138 A8

Dimensions International Standard

Section Width (mm)	418
Overall Diameter (mm)	1257
Static Loaded Radius (mm)	584
Rolling Circumference (mm)	3824
Rim Rec	W 13
Rim Alt	W 12 ; W 11
ECE	E11-106R-002974
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1025	1180	1355	1530	1705	1875	2030	2180
50	1080	1240	1420	1605	1790	1970	2130	2290
40	1110	1275	1465	1655	1845	2030	2195	2360
25	1215	1400	1605	1810	2020	2225	2405	2585
10	1540	1770	2030	2290	2555	2815	3045	3270

Printed on 22/09/2020 10:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..